

NORAM POWER SYSTEMS®



Model: **NPS P-20**

Ratings Range

Standby:	kw	16	20
	kva	20	25
Prime:	kw	14	18
	kva	17.5	22.5

Generator:	BCI184E
Voltage:	120/208-277/480
Phase:	3
Hertz:	60

105° Rise Prime Ratings:
kw/kva: 20/25 amps: 27



FEATURES

Perkins 35108 Water Cooled Diesel with Engine Safety Shutdowns

Battery with 12 Volt Electric Key Start

Voltage Selector Switch

120/240V 1-Phase, 120/280 3-Phase, 277/480 3-Phase

Control Panel with Analog Engine and Electrical Gauges

Distribution Panel with 120/240V Single-Phase Outlets with a Full Power 3-Phase Lug Panel

Sound Attenuated Gen-Set Enclosure with Sound Reduction Air-Inlet Baffles, Quiet Type Muffler

Skid Base Design with Built Fuel Tank Mounted within a Fuel Containment Cell (Tank Size for 24 Hours of Operating Run Time)

Skid Base Mounted to a Towable Trailer, Single Drop-Axle, 2200 lbs. with 15" Tires, Protective Fenders, Dual Safety Chains & DOT Running Lights

Gen-Set Enclosure Powder Coated Off-White (Standard)

Newage Generator - 311 Windings, 12-Wire Class H Insulation

432.563.9602

Sales
FAX 432.561.5622

Production
FAX 432.563.9606

9800 W. I-20
Midland, TX 79706